

**SADDLES**



- Direct Drill & Tap Saddle, Narrow Body Type
- Clamps, Saddles & Ferrule
- DN80-DN300
- For DI, MS & AC Pipes
- PN16
- Outlet, ½", ¾" & 1" BSP

**Option :**  
• Outlet 2" BSP, Broad Body Type (≥DN150 - DN300)



- Direct Drill & Tap Saddle, Broad Body Type
- Clamps, Saddles & Ferrule
- DN80-DN300
- For UPVC & MPVC Pipes
- PN16
- Outlet, ½", ¾" & 1" BSP

**Option :**  
• Outlet 2" BSP (≥ OD150)



- Direct Drill & Tap Saddle, Broad Body Type
- Clamps, Saddles & Ferrule
- OD63-OD355
- For PE, PVC-O, PVC-M & Other Plastic Pipes with Similar OD
- PN16
- Outlet, ½", ¾" & 1" BSP

**Option :**  
• Outlet 2" BSP (≥ OD110)

**CLAMPS**



- Stainless Steel Single Band Repair Clamp
- DN100-DN350
- EN 545
- For All Kind of Pipe Materials
- PN16
- Width: 200, 250, 300, 400, 450 & 600mm

**Option :**  
• Various Widths



- Stainless Steel Double Band Repair Clamp
- ≥ DN350
- EN 545
- For All Kind of Pipe Materials
- PN10
- Width: 300, 400, 450 & 600mm

**Option :**  
• Various Clamp Sizes & Widths

**FERRULE**



- Brass Ferrule Valve
- DN50 (2")
- JKR 20200-0174-04 & MS1396
- Threaded BSP
- PN10/16

**JOINT RESTRAINT SOLUTIONS**



- Poly Restraint Coupling
- Joint Restraint Solutions
- OD63-OD315
- For PE, PVC-O, PVC-M & Other Plastic Pipes with Similar OD
- PN16



- Poly Restraint Flange Adaptor
- Joint Restraint Solutions
- OD63-OD315
- For PE, PVC-O, PVC-M & Other Plastic Pipes with Similar OD
- PN16



- Large Diameter Poly Restraint Coupling
- Joint Restraint Solutions
- OD345-OD630
- For PE, PVC-O, PVC-M & Other Plastic Pipes with Similar OD
- PN16



- Large Diameter Poly Restraint Flange Adaptor
- Joint Restraint Solutions
- OD345-OD630
- For PE, PVC-O, PVC-M & Other Plastic Pipes with Similar OD
- PN16



- PE Quick Flange Adaptor
- Joint Restraint Solutions
- OD63-OD355
- For PE, PVC-O, PVC-M & Other Plastic Pipes with Similar OD
- PN16



- Uni-Flange Adaptor
- Joint Restraint Solutions
- DN80-DN400
- For DI Pipe
- PN16

**Option :**  
• For MS Pipe (≤DN300)



- Push-On Joint Restraint Harness
- Joint Restraint Solutions
- DN80-DN300
- For DI Socket Push-On Joints
- PN16

**HYDRANTS**



- 2-Way Pillar Hydrant
- Hydrants
- DN100
- JKR 20200-0042-99
- PN16
- Outlet Thread: V-Shaped



- Pillar-Hydrant Complete with Landing Valves
- Hydrants
- DN100
- JKR 20200-0042-99
- PN16
- Outlet: Female Instantaneous Coupler



- 3-Way Pillar Hydrant
- Hydrants
- DN150
- JKR 20200-0042-99
- PN16
- Outlet Thread: V-Shaped / Round



- Underground Hydrant
- Hydrants
- DN80
- BS 750
- PN10/PN16
- Screw Down Outlet : 65mm



- Sluice Valve Hydrant
- Hydrants
- DN80
- BS 750
- PN10/PN16
- Screw Down Outlet : 65mm



- Landing Valve Flanged End
- Hydrants
- DN65
- PN16
- Outlet: Female Instantaneous Coupler



- Landing Valve Screwed End
- Hydrants
- DN65
- PN16
- Outlet: Female Instantaneous Coupler

**MANHOLE COVERS**



- Manhole Cover (Model 668)
- Manhole Covers
- 710mm x 710mm x 100mm(H)
- BS EN 124-1&2 & SPAN-TS 3003
- D400
- Clear Opening: Ø600mm



- Manhole Cover with Frame & Extension Ring
- Manhole Covers
- 710mm x 710mm x 100mm(H)
- BS EN 124-1&2 & SPAN-TS 3003
- D400
- Clear Opening: Ø600mm



- Manhole Cover (Model 670H)
- Manhole Covers
- 840mm x 840mm x 100mm
- BS EN 124-1&2 & SPAN-TS 3003
- D400
- Clear Opening: Ø600mm



- Manhole Cover with Water Tight Seal (Model 670W)
- Manhole Covers
- 840mm x 840mm x 100mm(H)
- SPAN TS 3003
- D400
- Clear Opening: Ø600mm

**VALVE CHAMBER**



- Valve Chamber
  - 609mm
  - BS EN 124-1&2
  - C250 & D400
  - Clear Opening: Ø320mm
- Option :**  
• Extension Ring



**LYE MARKETING SDN. BHD.**

199701018201 (433698-D)

**A COMPLETE PIPING SOLUTION**

MANUFACTURER OF  
VALVES · HYDRANTS · JOINTS · FITTINGS · MANHOLE COVERS



**The Brand Of Reliability Since 1977**

**LYE MARKETING SDN.BHD.**

199701018201 (433698-D)

Sales & Marketing Office  
Lot 36, Jalan BRP 9/2b, Putra Industrial Park, Bukit Rahman Putra,  
47000 Sg. Buloh, Selangor.

Factory Tel. : 603 - 8961 1623  
Sales Tel. : 603 - 6140 3131 (Hunting Line)  
Mobile : 6012-277 3593

Email : enquiry@lye.com.my  
Website : https://lye.com.my/



Scan For More Info



**ABOUT US**



LYE Marketing Sdn Bhd, a wholly owned subsidiary of Engtex Group Berhad—listed on Bursa Malaysia since 2002—is a trusted player in Malaysia’s waterworks and infrastructure industry. The company specialises in supplying high-quality valves, hydrants, joints, fittings, and manhole covers for a wide range of applications.

Headquartered in Sungai Buloh, Selangor, LYE Marketing serves water authorities, contractors, developers, consultants, and utility providers across Malaysia and the region. Its products support water transmission and distribution systems, pipeline infrastructure, fire protection, and municipal engineering works.

With in-house manufacturing capabilities, the company ensures consistent supply, reliable performance, and timely project delivery. Operating under ISO 9001-certified quality management systems since 2002, its products

comply with Malaysian Standards and JKR specifications, and are certified by IKRAM, ANQAS, and SIRIM, as well as approved by Suruhanjaya Perkhidmatan Air Negara (SPAN).

LYE Marketing remains committed to delivering durable solutions and advancing sustainable infrastructure.

**SLUICE VALVES (GATE VALVES)**



- Resilient Seated**
  - Sluice Valves (Gate Valves)
  - DN50- DN1200
  - BS 5163 & BS EN 1171
  - PN10/16
  - Cap Top / Handwheel

- Option:**
- 1. By-pass (≥DN450)
  - 2. PN25



- Metal Seated**
  - Sluice Valves (Gate Valves)
  - DN50- DN1400
  - BS 5163 & BS EN 1171
  - PN10/16
  - Cap Top / Handwheel

- Option:**
- 1. By-pass ≥(DN450)
  - 2. Handwheel with Spur-Gear (≥D350)
  - 3. PN25

**BUTTERFLY VALVES**



- Double Eccentric Flanged**
  - Butterfly Valves
  - DN50- DN3000
  - BS EN 593
  - PN10/16
  - Worm Gear & Handwheel
  - IP65/IP68 Gear Box

- Option:**
- 1. Bare Shaft
  - 2. PN25



- Concentric Flanged**
  - Butterfly Valves
  - DN50- DN300
  - BS EN 593
  - Lever Type Operated

- Option:**
- Worm Gear & Handwheel



- Concentric Wafer Type**
  - Butterfly Valves
  - DN50 - 350mm
  - BS EN 593
  - PN10/16
  - Lever Type Operated ≤DN200

- Option:**
- Worm Gear & Handwheel ≥DN200

**AIR VALVES**



- Single Small Orifice**
    - Air Valves
    - DN20- DN25
    - JKR 20200 - 0097 - 01
    - PN16
    - ABS Float
    - Threaded BSP
- Option :**
- Gate Valve, Male Thread



- Automatic Air Relief**
  - Air Valves
  - DN25
  - BS EN 1074 - 4
  - PN 16
  - Stainless Steel / ABS Float
  - Threaded BSP/NPT

- Option :**
- Gate Valve, Male Thread



- Single Large Orifice**
  - Air Valves
  - DN50- DN100
  - JKR 20200 - 0097 - 01
  - PN10/16
  - ABS Float



- Double Orifice Standard**
  - Air Valves
  - DN50- DN200
  - JKR 20200 - 0097 - 01
  - BS EN 593
  - PN10/16
  - ABS Float
  - Integral Isolating Valve



- Double Orifice Kinetic**
  - Air Valves
  - DN50- DN200
  - JKR 20200 - 0097 - 01
  - PN10/16
  - ABS Float



- Aerokinetic Double Orifice**
  - Air Valves
  - DN50- DN200
  - BS EN 1074 - 4
  - PN10/16
  - Stainless Steel / ABS Float



- Dynamic Single Chamber Smart Air Valve**
  - Air Valves
  - DN50- DN250
  - BS EN 1074 - 4
  - PN10/16
  - Stainless Steel Float

**CHECK VALVES**



- Rubber Flap Type (Non-Slam)**
    - Check Valves
    - DN50- DN800
    - EN 12266-1
    - PN10/16
- Option :**
- PN25



- Double Door Wafer Type**
  - Check Valves
  - DN50- DN600
  - BS EN 12266-1 / BS EN 167167
  - PN16



- Globe Silent Type**
  - Check Valves
  - DN50- DN300
  - BS EN 12266
  - PN10/16

**STRAINERS**



- T-Pot Strainer**
  - Strainers
  - DN50- DN900
  - JKR 20200 - 0100 - 01
  - PN16



- Y-Strainer**
  - Strainers
  - DN50- DN350
  - JKR 20200 - 0100 - 01
  - PN16



- Rose-Strainer**
  - Strainers
  - DN100- DN900
  - PN16

**FOOT VALVE**



- Foot Valve**
  - DN50- DN300
  - BS EN 12266
  - PN16
  - Globe Type Body

**FLEXIBLE JOINTS**



- Mechanical Coupling**
    - Flexible Joints
    - DN80- DN800
    - For Ductile Iron Pipe
    - PN16
- Option**
- 1. For MS Pipe (≤DN300)
  - 2. Sleeve: 225mm (≤DN400)



- Mechanical Flange Adaptor**
  - Flexible Joints
  - DN80- DN800
  - For Ductile Iron Pipe
  - PN10/16
  - Universal Drilling (DN80- DN300)

- Option :**
- 1. For MS Pipe (≤DN300)
  - 2. Sleeve: 225mm (≤DN400)



- Stepped Coupling (PD)**
  - Flexible Joints
  - DN80- DN300
  - From PVC-O, PVC-M, PE to MS, UPVC Pipes
  - PN16

- Option :**
- Sleeve: 300mm (Selected Sizes)



- Stepped Coupling (PA)**
  - Flexible Joints
  - DN100- DN300
  - From PVC-O, PVC-M, PE to AC, MS(JKR) Pipes
  - PN16



- Universal Coupling**
  - Flexible Joints
  - DN80- DN600
  - For AC, MS, DI, UPVC, PVC-M, PVC-O, ABS Pipes
  - PN16
  - Wide OD Tolerance Range



- Univesal Flange Adaptor**
  - Flexible Joints
  - DN80- DN600
  - For AC, MS, DI, UPVC, PVC-M, PVC-O, ABS Pipes
  - PN10/16
  - Wide OD Tolerance Range
  - Universal Drilling (DN80- DN300)



- Long Collar Mechanical Coupling (PE)**
  - Flexible Joints
  - OD63- OD400
  - For PE, PVC-O & PVC-M Pipes
  - PN16
  - Sleeve: 300mm



- Dismantling Joint**
  - Flexible Joints
  - DN100- DN150
  - PN10/ PN16
  - Flanged Spigot + Flange Adaptor

**DETACHABLE JOINTS**



- Detachable Joint (DJ) Type A**
  - Detachable Joints
  - DN80- DN300
  - For AC & MS(JKR) Pipes
  - PN10/ PN16
  - O-Ring Gasket



- Detachable Joint (DJ) Type B**
  - Detachable Joints
  - DN80- DN300
  - For UPVC & MS Pipes
  - PN10/ PN16
  - O-Ring Gasket



- Variable Adaptor (VA)**
  - Detachable Joints
  - DN80- DN300
  - From AC, MS(JKR) to UPVC, MS Pipes
  - PN10/ PN16
  - Stepped Coupling
  - O-Ring Gasket

**BULK WATER METER SYSTEM**

